

NEW

Product Information

Wall-Mounted



Cooling Type

SANYO

SAP-K184GJL

SAP-K254GJL

















• Ionizer



SAP-C184GL
SAP-C254GL

Features

 <p>Microprocessor-controlled Operation Microprocessor control ensures that the temperature and humidity levels in the room are always comfortable.</p>	 <p>1-hour OFF Timer When this button is pushed either while the unit is operating or while it is stopped, the unit will operate for one hour and then switch off automatically.</p>	 <p>Powerful Start Function Cool your room so quickly at HH (Very High) Fan speed automatically for 5 minutes from the starting of operation. The HH Fan starts to rotate when the microcomputer in the air conditioner selects H (High) Fan speed during automatic operation.</p>
 <p>Automatic Fan Operation Convenient microprocessor control automatically adjusts fan speed to High, Medium or Low, according to room temperature to maintain a comfortable airflow throughout the room.</p>	 <p>Anti-mold Filter Filter is treated with anti-mold chemicals to prevent mold or bacteria from occurring.</p>	 <p>Economy Mode for Cooling Cooling and DRY Mode. With the Economy (Night Setback) Mode, the air conditioner automatically raises the temperature 1°C after 30 minutes, and then another 1°C after the next 30 minutes. This saves energy without sacrificing comfort and is ideal for gentle cooling.</p>
 <p>Air Sweep Control The air sweep function moves the flap up and down in the air outlet, directing air in a "sweeping" motion around the room and providing comfort in every corner.</p>	 <p>Automatic Restart Function for Power Failure Even when power failure occurs, preset programmed operation can be reactivated once power resumes.</p>	 <p>Air Clean Filter The dust-collecting Air Clean Filter is capable of efficiently catching dust and pollen. Attached to this is a ceramic filter which actively removes cigarette smoke and other unpleasant odors, providing clean, pleasant air.</p>
 <p>Flap Control Flaps can be manually set to the desired angle by remote control.</p>	 <p>Mild Dry By coupling compressor and fan operation, intermittent operation can be precisely controlled according to room temperature, so that air is efficiently dehumidified.</p>	 <p>Ionizer The Minus Ion that exist in the circumference of forest, a waterfall, and the fountain are generated blows off in the room.</p>
 <p>12-hour ON/OFF Timer This timer can be set to automatically turn the unit on or off at any time within a 12-hour period.</p>	 <p>Two Sensors Ensure Accurate and Comfortable Temperature Control Room temperature can be monitored by either the sensor located in the air conditioner or remote control unit.</p>	

Wall-Mounted Cooling Type

(Tentative)

Model No.	Indoor Unit		SAP-K184GJL		SAP-K254GJL		
	Outdoor Unit		SAP-C184GL		SAP-C254GL		
SPECIFICATIONS	Performance		Cooling		Cooling		
	Capacity	kW	5.30		7.05		
	Air-circulation	Hi m ³ /h	1,000		1,050		
	Moisture removal	Hi Liters/h	2.30		3.30		
	Electrical Ratings		1φ, 50Hz		1φ, 50Hz		
	Voltage rating	V	220-240		220-240		
	Available voltage range	V	198-264		198-264		
	Running amperes	A	8.9/9.3/10.1		12.5/12.6/12.8		
	Power input	W	1,860/1,950/2,080		2,600/2,660/2,730		
	Power factor	%	95/91/86		95/92/89		
	C.O.P.	W/W	2.85/2.72/2.55		2.71/2.65/2.58		
	Operating noise	IN dB-A	43		45		
		OUT dB-A	55		57		
	Features						
	Controls	Microcomputer					
Compressor	Rotary						
Fan Speed	3 Speed + Auto						
Timer	ON/OFF 12 Hour						
Air deflection	Horizontal	Manual					
	Vertical	Auto Flap					
Air filter	Washable						
Air clean filter	Dust-Collecting & Deodorizing						
Ionizer	Ionizer (Synchronization with Compressor)						
Panel	Washable						
Remote controller	With Holder / Address SW						
Max. tube length at shipment	m	7.5		10			
Ref. dia. Na/Wi. Pipe	mm (in)	6.35 (1/4) / 12.7 (1/2)		6.35 (1/4) / 15.88 (5/8)			
Cabinet Dimensions							
Indoor Unit	Height	mm	298				
	Width	mm	1,065				
	Depth	mm	218				
Outdoor Unit	Height	mm	670				
	Width	mm	880				
	Depth	mm	285				
	Net weight	kg	44		55		

*Specifications subject to change without notice.

Cooling	
Indoor air temperature	27°CDB/19°CWB
Outdoor air temperature	35°CDB/24°CWB

Distributed by:

SANYO

SANYO Airconditioners Manufacturing (S) Pte Ltd
6 Commonwealth Lane, #03-01/02 GMTI Building,
Singapore 149547
Tel: (+65) 6265 7777 Fax: (+65) 6265 6856